

TYPE 3 FLAT EYE




TYPE 4 TWISTED EYE



TYPE 3 (EEF) FLAT EYE SLINGS ARE VERY POPULAR AND CAN BE USED IN ALL THREE TYPES OF HITCHES. THEY ARE EASIER TO REMOVE FROM BENEATH THE LOAD AFTER THE LOAD IS IN PLACE. UNLESS TYPE 4 IS REQUESTED, TYPE 3 WILL BE SUPPLIED AS THE STANDARD EE SLING.

TYPE 4 (EET) TWISTED EYE SLINGS ARE SIMILAR TO TYPE 3, EXCEPT THE EYES ARE TURNED 90° TO FORM A BETTER CHOKER HITCH. THIS TYPE OF EYE ALSO NESTS TOGETHER BETTER ON THE CRANE HOOK WHEN USED IN A BASKET HITCH.




TYPE 5 ENDLESS



TYPE 5 (EN) ENDLESS SLINGS IS THE MOST VERSATILE SLING THAT CAN BE USED IN VERTICAL, CHOKER, OR BASKET HITCHES. THE HOOK AND LOAD CONTACT POINTS CAN BE ROTATED TO EXTEND THE LIFE OF THE SLING. THE SLING LEGS CAN BE SPREAD FOR IMPROVED LOAD CONTROL.

	RATED CAPACITY IN LBS.				
	TYPE 3	TYPE 4	VERTICAL	CHOKER	BASKET
	EEF	EET			
ONE PLY	1-901		1600	1280	3200
	1-901.5		2300	1840	4600
	1-902		3100	2480	6200
	1-903		4700	3760	9400
	1-904		6200	4960	12400
	1-905		7800	6240	15600
	1-906		9300	7440	18600
	1-908		11800	9440	23600
	1-910		14700	11760	29400
	1-912		17600	14080	35200
TWO PLY	2-901		3100	2480	6200
	2-901.5		4700	3760	9400
	2-902		6200	4960	12400
	2-903		8800	7040	17600
	2-904		11000	8800	22000
	2-905		13700	10960	27400
	2-906		16500	13200	33000
	2-908		22700	18160	45400
	2-910		28400	22720	56800
	2-912		34100	27280	68200
THREE PLY	3-901		4700	3760	9400
	3-901.5		7000	5600	14000
	3-902		9300	7440	18600
	3-903		13500	10800	27000
	3-904		17200	13760	34400
	3-905		20600	16480	41200
	3-906		24400	19520	48800
	3-908		30700	24580	61400
	3-910		36000	28800	72000
	3-912		40300	32260	80600
FOUR PLY	4-901		5500	4400	11000
	4-901.5		9400	7520	18800
	4-902		11000	8800	22000
	4-903		16400	13120	32800
	4-904		20400	16320	40800
	4-905		25500	20400	51000
	4-906		30600	24480	61200
	4-908		41000	32800	82000
	4-910		48000	38400	96000
	4-912		60000	48000	120000

TYPES 3 AND 4 EYES ARE TAPERED AT 3" AND WIDER UNLESS OTHERWISE ORDERED. EYE LENGTH AND WIDTH VARY WITH SLING WIDTH AND NUMBER OF WEBBING PLYS. NOTE: ANGLES MAY AFFECT CAPACITY OF SLING. SEE SLING ANGLE CHART.

	TYPE 5 EN	RATED CAPACITY IN LBS.		
		VERTICAL	CHOKER	BASKET
				
ONE PLY	1-901	3200	2560	6400
	1-901.5	4600	3680	9200
	1-902	6200	4960	12400
	1-903	9400	7520	18800
	1-904	12400	9920	24800
	1-905	15600	12480	31200
	1-906	18600	14880	37200
	1-908	21200	16960	42400
	1-910	26500	21200	53000
	1-912	31800	25440	63600
TWO PLY	2-901	6200	4960	12400
	2-901.5	9400	7520	18800
	2-902	12400	9920	24800
	2-903	17600	14080	35200
	2-904	22000	17600	44000
	2-905	27400	21920	54800
	2-906	33000	26400	66000
	2-908	42300	33840	84600
	2-910	52900	42320	105800
	2-912	63500	50800	127000
THREE PLY	3-901	9600	7680	19200
	3-901.5	13700	10940	27400
	3-902	17700	14160	35400
	3-903	26600	21310	53200
	3-904	34600	27650	69200
	3-905	42000	33600	84000
	3-906	48900	39120	97800
	3-908	61400	49150	122800
	3-910	72000	57600	144000
	3-912	80600	64510	161200
FOUR PLY	4-901	11000	8800	22000
	4-901.5	18200	14590	36400
	4-902	22000	17600	44000
	4-903	32900	26320	65800
	4-904	40800	32640	81600
	4-905	51000	40800	102000
	4-906	61200	48960	122400
	4-908	81900	65540	163800
	4-910	96000	76800	192000
	4-912	107000	85600	214000

TYPE 5 EYES ARE TAPERED AT 3" AND WIDER UNLESS OTHERWISE ORDERED. THESE WIDER SLINGS ARE TAPERED AT THE BEARING POINTS TO ACCOMMODATE A CRANE HOOK.

NOTE: ANGLES MAY AFFECT CAPACITY OF SLING. SEE SLING ANGLE CHART.

WARNING DO NOT EXCEED RATED CAPACITIES

F.O.B. WAREHOUSE