



## BIG EASY HIGH PERFORMANCE ROUND SLING



Overall Length



High Performance Roundslings are constructed using a continuous loop of UHMPE core yarns encased in a texturized nylon, double wall cover. This heavy duty cover helps to protect the load bearing core yarn from abrasion and increase the life of the sling.

### Features & Benefits:

- Vertical, Choker & Basket Hitch
- Vertical Capacities from 10,000 lbs. to 500,000 lbs.
- Load bearing points can be rotated to extend life
- Lightweight: Ease of use compared to wire rope and chain
- Low Stretch: Approximately 1% at rated capacity
- Highest capacity for the lightest weight
- Texturized Nylon Double Wall, Seamless Cover
  - » Helps protect core yarn from UV degradation
  - » Soft cover helps to prevent scratches to load surface
- Two sliding wear sleeves standard on all BHP slings

### Manufacturing Tolerance:

+/-1" + 2% of specified length

| Size   | RATED CAPACITY IN POUNDS |         |               |               | Min. Length | Body DIA Relaxed (in.) | Width at Load (in.) | Weight Per Foot (lbs.) | Min. Hardware Diameter (in.) |
|--------|--------------------------|---------|---------------|---------------|-------------|------------------------|---------------------|------------------------|------------------------------|
|        | Vertical                 | Choker  | Basket At 90° | Basket At 45° |             |                        |                     |                        |                              |
| BHP10  | 10,000                   | 8,000   | 20,000        | 14,100        | 4'          | 1.00                   | 1.60                | 0.45                   | 0.69                         |
| BHP20  | 20,000                   | 16,000  | 40,000        | 28,000        | 4'          | 1.25                   | 2.00                | 0.55                   | 1.06                         |
| BHP30  | 30,000                   | 24,000  | 60,000        | 42,000        | 6'          | 1.40                   | 2.13                | 0.70                   | 1.44                         |
| BHP40  | 40,000                   | 32,000  | 80,000        | 56,000        | 6'          | 1.75                   | 2.75                | 0.82                   | 1.50                         |
| BHP50  | 50,000                   | 40,000  | 100,000       | 70,000        | 8'          | 1.90                   | 2.88                | 1.02                   | 1.75                         |
| BHP60  | 60,000                   | 48,000  | 120,000       | 84,000        | 8'          | 2.00                   | 3.13                | 1.15                   | 2.00                         |
| BHP70  | 70,000                   | 56,000  | 140,000       | 98,000        | 8'          | 2.15                   | 3.25                | 1.29                   | 2.19                         |
| BHP80  | 80,000                   | 64,000  | 160,000       | 113,000       | 8'          | 2.25                   | 3.50                | 1.5                    | 2.38                         |
| BHP90  | 90,000                   | 72,000  | 180,000       | 127,000       | 10'         | 2.50                   | 3.88                | 1.64                   | 2.38                         |
| BHP100 | 100,000                  | 80,000  | 200,000       | 141,000       | 10'         | 2.75                   | 4.25                | 1.77                   | 2.50                         |
| BHP125 | 125,000                  | 100,000 | 250,000       | 176,000       | 10'         | 3.00                   | 4.88                | 2.15                   | 2.63                         |
| BHP150 | 150,000                  | 120,000 | 300,000       | 210,000       | 10'         | 3.25                   | 5.25                | 2.49                   | 2.88                         |
| BHP175 | 175,000                  | 140,000 | 350,000       | 240,000       | 10'         | 3.50                   | 5.75                | 3.12                   | 3.13                         |
| BHP200 | 200,000                  | 160,000 | 400,000       | 280,000       | 10'         | 3.75                   | 6.13                | 3.46                   | 3.38                         |

\* Capacities available up to 500,000 lbs. in a Vertical Hitch. Please contact our office for a quote and more information on larger sizes



**WARNING:** Do not exceed rated capacities. Sling capacity decreases as the angle from horizontal decreases. Slings should never be used at angles less than 30 degrees.