

## HEAD IRONS



- Used to suspend lowering-in belts
- Painted, Alloy steel bail w/ Stainless Steel Data Plate
- Lowering-in Belt not included

			Lifting Eye Size	Approx. Weight
Part #	Head Iron Hooks	Fits Lowering-In Belt #	in. width x length	Lbs.
ASHI-2	2	ASLB-2-12	4.75" x 6.25"	45
ASHI-4	3	ASLB-3-18	4.75" x 6.25"	78
ASHI-5	4	ASLB-4-24	4.75" x 6.25"	110
ASHI-06	5	ASLB-5-30	4.75" x 6.25"	147
ASHI-07	6	ASLB-6-36	6.5" x 9"	180
ASHI-08	7	ASLB-7-42	6.5" x 9"	215
ASHI-09	8	ASLB-8-48	6.5" x 9"	230
ASHI-11	9	ASLB-9-54	6.5" x 9"	275

\* 5 to 1 design factor standard

Designed to meet or exceed: ASME B30.20 Below-the-Hook Lifting Devices  
AWS D 14.1 Welding Procedures

## LOWERING-IN BELTS



\*Head Iron not included as pictured

Part #	# of Eyes	# of Slings	Max Pipe Dia.	Belt Width in.	Belt Length in.	Approx. Weight Lbs	Rated Capacity Lbs
ASLB-2-12	2	1	12"	12"	4'-9"	32	48,000
ASLB-3-18	3	3	18"	18"	7'-0"	52	73,000
ASLB-4-24	4	4	20"	24"	8'-6"	81	97,000
ASLB-5-30	5	5	24"	30"	10'-0"	90	122,000
ASLB-6-36	6	6	30"	36"	11'-6"	120	146,000
ASLB-7-42	7	7	36"	42"	13'-6"	135	171,000
ASLB-8-48	8	8	42"	48"	15'-0"	170	195,000
ASLB-9-54	9	9	48"	54"	17'-0"	225	228,000

\* 5 to 1 design factor standard

Designed to meet or exceed: ASME B30.9 Slings  
AWS D 14.1 Welding Procedures

- Made with Heavy Duty Webbing (coating available upon request)
- Durable Private Labeled Tagging
- Painted, Alloy steel end irons
- Lowering-in belt and head iron sold separately



**WARNING:** Do not exceed rated capacities. Sling capacity decreases as the angle from horizontal decreases. Slings should never be used at angles less than 30 degrees.