



BIG EASY ROUNDSLING

A Roundsling is constructed using a continuous loop of core yarns encased in a double wall cover. This cover helps to protect the load bearing yarn from abrasion.

Features & Benefits:

- Vertical, Choker & Basket Hitch
- Vertical Capacities from 2,600 lbs. to 110,000 lbs.
- Load bearing points can be rotated to extend life
- Lightweight: Easy to use, versatile, high strength-to-weight ratio
- Low Stretch: Approximately 3% at rated capacity
- Color Coded by Capacity: Allows for quick identification
- Double Wall, Seamless Cover
 - » Helps protect core yarn from UV degradation
 - » Soft cover helps to prevent scratches to load surface

Manufacturing Tolerance (applies to roundslings when new, at the time of final manufacture):

- 13,200 lbs. or less – +/-1" + 1% of specified length
- Higher than 13,200 lbs. up to 53,000 lbs. – +/-2" + 1% of specified length
- Higher than 53,000 lbs.. – +/-3" + 1% of specified length



Overall Length



Matched Set Length Tolerance: When multiple legs of a bridle sling are made, or when multiple slings are prescribed to be made within a Matched Set Tolerance, their length variance from their nominal length shall remain within a dimension equal to one-half of their corresponding Standard Length Tolerance Values.

Measurement Method: Roundsling length is measured with the sling laid flat while being manually pulled taut.

Part #	Color Code	RATED CAPACITY IN POUNDS				Minimum Length	Weight Per Foot (lbs.)	Body DIA Relaxed
		Vertical	Choker	Basket At 90°	Basket At 45°			
BRS30	PURPLE	2,600	2,100	5,200	3,600	2'	0.2	5/8"
BRS60	GREEN	5,300	4,240	10,600	7,400	2'	0.3	7/8"
BRS90	YELLOW	8,400	6,700	16,800	11,800	2'	0.5	1 1/8"
BRS120	TAN	10,600	8,500	21,200	14,000	2'	0.6	1 1/8"
BRS150	RED	13,200	10,600	26,400	18,000	3'	0.8	1 3/8"
BRS180	WHITE	16,800	13,400	33,600	23,000	3'	0.9	1 3/8"
BRS240	BLUE	21,200	17,000	42,400	29,000	3'	1.3	1 3/4"
BRS300	ORANGE	25,000	20,000	50,000	35,000	4'	1.5	2"
BRS360	GREY	31,000	24,800	62,000	43,300	4'	1.7	2 1/4"
BRS400	ORANGE	40,000	32,000	80,000	56,500	6'	2.2	2 1/2"
BRS600	BROWN	53,000	42,400	106,000	74,000	6'	2.8	2 3/4"
BRS800	OLIVE	66,000	52,800	132,000	93,000	6'	3.4	3 1/8"
BRS1000	BLACK	90,000	72,000	180,000	127,000	6'	4.3	3 5/8"
BRS1100	BLACK	100,000	80,000	200,000	141,000	6'	4.83	4 1/4"
BRS1200	BLACK	110,000	88,000	220,000	155,000	8'	5.28	4 1/2"

* Larger Capacities Available. Please contact our office for a quote and more information.



WARNING: Do not exceed rated capacities. Sling capacity decreases as the angle from horizontal decreases. Slings should never be used at angles less than 30 degrees.